# Jointing & Rebating Cutters.


# 3 + 3 Wing

## **Application:**

Allows jointing and or rebating operations to be carried out on spindle moulders or multi head machines.

Both sides of head have seats for scribes, allowing LH & RH operation, producing sharp clean cuts.

Recommended for mechanical feed.




## **Technical Details:**

All steel construction. Anti-rust finish on all parts. Balanced design for smooth running.

**CROWN TOOL** 

Bores to H7 tolerance. Positive insert location.



### Sizes Available

CODE	D	d	w	Insert Size	Insert Size
CODE	<u> </u>	u	VV	ilisert Size	ilisert Size
SJR-1253012-1 <sup>1</sup> / <sub>4</sub>	125	11/4	30	30 x 12 x 1.5	14 x 14 x 2
SJR-1254012-1 <sup>1</sup> / <sub>4</sub>	125	11/4	40	40 x 12 x 1.5	14 x 14 x 2
SJR-1255012-1 <sup>1</sup> / <sub>4</sub>	125	11/4	50	50 x 12 x 1.5	14 x 14 x 2
SJR-1253012-40	125	40	30	30 x 12 x 1.5	14 x 14 x 2
SJR-1254012-40	125	40	40	40 x 12 x 1.5	14 x 14 x 2
SJR-1255012-40	125	40	50	50 x 12 x 1.5	14 x 14 x 2
SJR-1503012-1 <sup>1</sup> / <sub>4</sub>	150	11/4	30	30 x 12 x 1.5	14 x 14 x 2
SJR-1504012-1 <sup>1</sup> / <sub>4</sub>	150	11/4	40	40 x 12 x 1.5	14 x 14 x 2
SJR-1505012-1 <sup>1</sup> / <sub>4</sub>	150	11/4	50	50 x 12 x 1.5	14 x 14 x 2
SJR-1503012-40	150	40	30	30 x 12 x 1.5	14 x 14 x 2
SJR-1504012-40	150	40	40	40 x 12 x 1.5	14 x 14 x 2
SJR-1505012-40	150	40	50	50 x 12 x 1.5	14 x 14 x 2
SJR-1804012-SHR-1 <sup>1</sup> / <sub>4</sub>	180	11/4	40	40 x 12 x 1.5	14 x 14 x 2
SJR-1804012-SHR-40	180	40	40	40 x 12 x 1.5	14 x 14 x 2

## **Spare Parts:**

Scribes	14 x 14 x 2 Scribe
Insert screw	M6 x 16 TH
Wedge 30 x 12	W3012-TS-T3
Wedge 40 x 12	W4012-TS-T3
Wedge 50 x 12	W5012-TS-T3
Scribe Screw	SS-M5-12
Key	5A/F-TEE

# **Glue Joint Cutters**

# 3 Wing

## **Application:**

For cutting of edge glue joints when joining solid timber boards.

Wood thickness from 16mm to 60mm. Particularly suitable for "brittle" timbers where glue butt joints may not be strong enough. Recommended for mechanical feed.

## **Technical Details:**

All aluminum construction. Anti-rust finish on all parts. Balanced design for smooth running.

Bores to H7 tolerance. Positive insert location.




Sizes Available

### CODE. D d **Teeth Insert** SGJ-140 5025-2T-11/4 or 40 2 50 x 25 x 2 P144 140 11/4 or 40 50 3 SGJ-150 5025-3T-1<sup>1</sup>/<sub>4</sub> or 40 150 11/4 or 40 50 50 x 25 x 2 P1772 **SGJ-150 6025-4T-1**<sup>1</sup>/<sub>4</sub> or 40 150 11/4 or 40 60 4 60 x 25 x 2 P1773



Wedge WSGJ 5025-TS-T3 Clamp Screw M6 x 20 End Stop M4x9HD Key 5A/F TEE Adjust Screw M6 x 16 GJS



## Special Features

Tongue and groove profile ensures positive location of boards. Micro adjustment of profile inserts allows tight, standard or loose fit as required. Precision ground profile knives ensure consistent profile accuracy.